

علامت اختصاری	اندازه به میلی‌متر											A	G	e ₁	مساحت گشتاور درجه دوم			ممان استاتیکی	
	K	b ₁	b ₂	b ₃	f ₁	f ₂	f ₃	h ₁	h ₂	h ₃	r ₁				I _y	W _y	I _z	W _z	I _r
	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	cm ²	kg/m	cm	cm ⁴	cm ³	cm ⁴	cm ³	cm ⁴
												F		e _x					

A	ریل بالابر طبق DIN 536 با در نظر گرفتن فرستیش سر ریل a تا 25% از مقدار h ₃																		
45	45	125	54	24	14.5	11	8	50±1	19	15	4	26.1	20.5	3.07	68.1	22.1	165	26.4	49.8
55	55	150	66	31	17.5	12.5	9	59±1	22.5	19	5	37.4	29.4	3.60	136	37.8	328	43.7	105
65	65	175	78	38	20	14	10	68±1	27	23	6	50.9	40.0	4.11	244	59.4	593	67.8	200
75	75	200	90	45	22	15.4	11	77±1	31.5	27	8	66.1	51.9	4.62	406	88.0	985	98.5	343
100	100	200	100	60	23	16.5	12	85±1.5	35.5	30	10	85.6	76.2	4.76	642	135	1270	127	702
120	120	220	120	72	30	20	14	93±1.5	43.5	35.5	10	115	90.3	5.15	992	193	2190	199	1374

